

Part number

MAPN 06 L32



Surface mounting housing, LS-TYPE series, with 1 lever, M32 cable entry, size "44.27", high construction

Product description

Product type	Surface mounting housing
Series	LS-TYPE
Closing type	With 1 lever
Size	Size 44.27
Cable entry	With cable entry M32
Specification	High construction

Technical data

IP degree of protection	IP65
Further technical details	
Weight	300,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163118
eCl@ss 8.1	27440202
ETIM 7.0	EC000437


Packaging Information

Packaging length	475,00 mm
Packaging height	200,00 mm
Packaging width	150,00 mm
Packaging weight	3,20 kg
Packaging volume	14,25 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747248778
Sub-packaging weight	1,60 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187640

Part number MAPN 06 L32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "44.27" LS-TYPE version

<p>inserts: page</p> <p>CDD 24 poles + ⊕ 59 *</p> <p>CQE 10 poles + ⊕ 80 *</p> <p>CSH 6 poles + ⊕ 88 *</p> <p>CCE 6 poles + ⊕ 94 *</p> <p>CNE, CSE, JONE, JOSE 6 poles + ⊕ 95 and 103 *</p> <p>CSS 6 poles + ⊕ 118 *</p> <p>CTE, CTSE (**) 6 poles + ⊕ 126 *</p> <p>MIXO 2 modules 160+195 *</p> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p> housings with single lever</p>	<p> hoods with 2 pegs</p>																			
<table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 50%; text-align: left;">description</th> <th style="width: 25%; text-align: left;">part no.</th> <th style="width: 25%; text-align: left;">entry</th> </tr> <tr> <td>bulkhead mounting housing, with lever</td> <td>CHIN 06 L</td> <td>M</td> </tr> <tr> <td>surface mounting housing, high construction, with lever</td> <td>MAPN 06 L32</td> <td>32</td> </tr> </table>	description	part no.	entry	bulkhead mounting housing, with lever	CHIN 06 L	M	surface mounting housing, high construction, with lever	MAPN 06 L32	32		<table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 50%; text-align: left;">part no.</th> <th style="width: 25%; text-align: left;">entry</th> </tr> <tr> <td>MHON 06 L25</td> <td>25</td> </tr> <tr> <td>MFON 06 L25</td> <td>25</td> </tr> <tr> <td>MHVN 06 L25</td> <td>25</td> </tr> <tr> <td>MFVN 06 L25</td> <td>25</td> </tr> </table>	part no.	entry	MHON 06 L25	25	MFON 06 L25	25	MHVN 06 L25	25	MFVN 06 L25	25
description	part no.	entry																			
bulkhead mounting housing, with lever	CHIN 06 L	M																			
surface mounting housing, high construction, with lever	MAPN 06 L32	32																			
part no.	entry																				
MHON 06 L25	25																				
MFON 06 L25	25																				
MHVN 06 L25	25																				
MFVN 06 L25	25																				
<p>with pegs, side entry with pegs, side entry, high construction</p> <p>with pegs, top entry with pegs, top entry, high construction</p> <p>(**) only in the CHIN 06 L enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>dimensions in mm</p> <p>CHIN 06 L</p> <p>MAPN 06 L32</p>	<p>dimensions in mm</p> <p>MFON 06 L25</p> <p>MFVN 06 L25</p> <p>MHON 06 L25</p> <p>MHVN 06 L25</p>																			
<p>dimensions shown are not binding and may be changed without notice</p>	<p>4</p>																				