

Part number

MFVN 06 L25



Hood, LS-TYPE series, with 2 pegs, M25 top cable entry without adapter, size "44.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 2 pegs
Size	Size 44.27
Cable entry	Top cable entry M25
Specification	High construction

Technical data

IP degree of protection	IP65
Further technical details	
Weight	0,50 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163163
eCl@ss 8.1	27440202
ETIM 7.0	EC000437


Packaging Information

Packaging length	175,00 mm
Packaging height	195,00 mm
Packaging width	260,00 mm
Packaging volume	8,87 dm ³
Packaging description	Carton box
Packaging quantity	20 Pcs
Packaging EAN code	8015747187763
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187770

Part number MFVN 06 L25



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "44.27" LS-TYPE version

<p>inserts: page</p> <p>CDD 24 poles + ⊕ 59 *</p> <p>CQE 10 poles + ⊕ 80 *</p> <p>CSH 6 poles + ⊕ 88 *</p> <p>CCE 6 poles + ⊕ 94 *</p> <p>CNE, CSE, JONE, JOSE 6 poles + ⊕ 95 and 103 *</p> <p>CSS 6 poles + ⊕ 118 *</p> <p>CTE, CTSE **) 6 poles + ⊕ 126 *</p> <p>MIXO 2 modules 160+195 *</p> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p> housings with single lever</p>	<p> hoods with 2 pegs</p>
description	part no. entry	part no. entry
bulkhead mounting housing, with lever	CHIN 06 L	
surface mounting housing, high construction, with lever	MAPN 06 L32 32	
with pegs, side entry		MHON 06 L25 25
with pegs, side entry, high construction		MFON 06 L25 25
with pegs, top entry		MHVN 06 L25 25
with pegs, top entry, high construction		MFVN 06 L25 25
**) only in the CHIN 06 L enclosure		
panel cut-out for bulkhead mounting housing in mm	dimensions in mm	dimensions in mm
<p style="font-size: x-small;">- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>CHIN 06 L</p> <p>MAPN 06 L32</p>	<p>MFON 06 L25</p> <p>MFVN 06 L25</p> <p>MHON 06 L25</p> <p>MHVN 06 L25</p>
	dimensions shown are not binding and may be changed without notice	