

Part number

MHVN 06 LG25



Hood, LS-TYPE series, with 1 lever, M25 top cable entry, size "44.27"

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 1 lever
Size	Size 44.27
Cable entry	Top cable entry M25

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	124,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747194341
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Sub-packaging weight	0,62 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747194358

Part number

MHVN 06 LG25



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures		size "44.27"	LS-TYPE version																					
<p>inserts:</p> <table border="0"> <tr> <td>CDD</td> <td>24 poles + @</td> <td>59 *</td> </tr> <tr> <td>CQE</td> <td>10 poles + @</td> <td>80 *</td> </tr> <tr> <td>CSH</td> <td>6 poles + @</td> <td>88 *</td> </tr> <tr> <td>CCE</td> <td>6 poles + @</td> <td>94 *</td> </tr> <tr> <td>CNE, CSE, JONE, JCSE</td> <td>6 poles + @ 95 and 103</td> <td>118 *</td> </tr> <tr> <td>CSS</td> <td>6 poles + @</td> <td>118 *</td> </tr> <tr> <td>MIXO</td> <td>2 modules</td> <td>160+195 *</td> </tr> </table> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	CDD	24 poles + @	59 *	CQE	10 poles + @	80 *	CSH	6 poles + @	88 *	CCE	6 poles + @	94 *	CNE, CSE, JONE, JCSE	6 poles + @ 95 and 103	118 *	CSS	6 poles + @	118 *	MIXO	2 modules	160+195 *	<p>hoods with 2 pegs</p>	<p>covers</p>	
CDD	24 poles + @	59 *																						
CQE	10 poles + @	80 *																						
CSH	6 poles + @	88 *																						
CCE	6 poles + @	94 *																						
CNE, CSE, JONE, JCSE	6 poles + @ 95 and 103	118 *																						
CSS	6 poles + @	118 *																						
MIXO	2 modules	160+195 *																						
<p>description</p> <p>with lever and gasket, top entry with lever and gasket, top entry, high construction</p> <p>covers with pegs covers with lever</p>	<p>part no.</p> <p>entry M</p> <p>MHVN 06 LG25 25 MFVN 06 LG25 25</p>	<p>part no.</p> <p>CHCN 06 L CHCN 06 LG</p>																						
	<p>dimensions in mm</p> <p>MHVN 06 LG25</p> <p>MFVN 06 LG25</p>	<p>dimensions in mm</p> <p>CHCN 06 L</p> <p>CHCN 06 LG</p>																						
	<p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>																							
	<p>IP65</p> <p>dimensions shown are not binding and may be changed without notice</p>																							