

Part number

# MHVN 16.32



Hood, LS-TYPE series, with 4 pegs, M32 top cable entry, size "77.27"

#### Product description

<b>Product type</b>	Hood
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 4 pegs
<b>Size</b>	Size 77.27
<b>Cable entry</b>	Top cable entry M32

#### Technical data

**IP degree of protection** IP65

#### Further technical details

<b>Weight</b>	126,00 g
<b>Operating temperature range (min, max)</b>	-40°C...+125°C

#### Material properties

<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747194280
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437


#### Packaging Information

<b>Sub-packaging weight</b>	0,63 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747194297

# Part number MHVN 16.32



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures** size "77.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD .....	40 poles + @ 49+52 *		
CT, CTS **)	40 poles + @ 56 *		
CDD .....	72 poles + @ 62+65 *		
CDE .....	32 poles + @ 82+84 *		
CSH .....	16 poles + @ 90+92 *		
CCE .....	16 poles + @ 98+102 *		
CNE, CSE, JCNE, JCSE	16 poles + @ 99 and 108 *		
CSS .....	16 poles + @ 120+122 *		
CTE, CTSE **)	16 poles + @ 128 *		
CMSE .....	6+2 (aux) poles + @ 137 *		
CMCE .....	6+2 (aux) poles + @ 136 *		
CP .....	6 poles + @ 149+150 *		
CX .....	6/36 e 12/2 poles + @ 152+153 *		
CX .....	4/0 e 4/2 poles + @ 154 *		
MIXO .....	4 modules 160-195 *		

insert centre distance: 77,5 x 27 mm  
\* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	<b>CHIN 16</b>	M		
surface mounting housing, high construction, with 2 levers	<b>MAPN 16.32</b>	32		
with pegs, side entry			<b>MHON 16.32</b>	32
with pegs, side entry, high construction			<b>MFON 16.32</b>	32
with pegs, top entry			<b>MHVN 16.32</b>	32
with pegs, top entry, high construction			<b>MFVN 16.32</b>	32

\*\*) only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm	CHIN 16	MAPN 16.32	MFON 16.32	MHON 16.32	MHVN 16.32
Front view	130, 29, 103, 115.5	130, 81, 105, 117	130, 93.5	130, 93.5	130, 93.5
Side view	58, 6, 32, 45.5	58, 4, 45, 57	58, 76, 43	58, 76, 43	58, 76, 43
Top view	130, 58, 32, 45.5	130, 58, 81, 45, 57	130, 58, 93.5, 43	130, 58, 93.5, 43	130, 58, 93.5, 43