

Part number

# MHVN 24 G32




Hood, LS-TYPE series, with 2 levers, M32 top cable entry, size "104.27"

Product description		Material properties	
<b>Product type</b>	Hood	<b>Other materials</b>	Lever: Polyamide (PA) Gasket: NBR
<b>Series</b>	LS-TYPE	<b>Colour</b>	RAL 9005 black
<b>Closing type</b>	With 2 levers	<b>RoHs conformity</b>	Compliant
<b>Size</b>	Size 104.27	<b>China RoHs - EFUP</b>	E
<b>Cable entry</b>	Top cable entry M32	<b>REACH SVHC substances</b>	No
Technical data		Approvals / Standards	
<b>IP degree of protection</b>	IP65	<b>Certifications</b>	DNV, BV
Further technical details		<b>UL</b>	ECBT2
<b>Weight</b>	248,00 g	<b>cUL</b>	ECBT8
<b>Operating temperature range (min, max)</b>	-40°C...+125°C	General ordering information	
		<b>EAN13 code</b>	8015747194402
		<b>eCl@ss 8.1</b>	27440202
		<b>ETIM 7.0</b>	EC000437
		Packaging Information	
		<b>Sub-packaging weight</b>	1,24 kg
		<b>Sub-packaging description</b>	Plastic packaging
		<b>Sub-packaging quantity</b>	5 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747194419

# Part number MHVN 24 G32



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures		size "104.27"	LS-TYPE version
<p>inserts: page</p> <p>CD ..... 64 poles + @ 51+53 *</p> <p>CDD ..... 108 poles + @ 64+66 *</p> <p>CQE ..... 46 poles + @ 83+85 *</p> <p>CSH ..... 24 poles + @ 91+93 *</p> <p>CCE ..... 24 poles + @ 100+104 *</p> <p>CNE, CSE, JONE, JCSE 24 poles + @ 101 and 109 *</p> <p>CSS ..... 24 poles + @ 121+123 *</p> <p>CMSE ..... 10+2 (aux) poles + @ 139 *</p> <p>CMCE ..... 10+2 (aux) poles + @ 138 *</p> <p>CX ..... 4/8 poles + @ 155 *</p> <p>MIXO ..... 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p>		<p>hoods with 4 pegs</p>	<p>covers</p>
description	part no.	entry	part no.
with 2 levers and gasket, top entry	MHVN 24 G32	32	CHCN 24
with 2 levers and gasket, top entry, high construction	MFVN 24 G32	32	CHCN 24 G
covers with pegs			
covers with 2 levers			
	<p>dimensions in mm</p> <p><b>MHVN 24 G32</b></p> <p><b>MFVN 24 G32</b></p>		<p>dimensions in mm</p> <p><b>CHCN 24</b></p> <p><b>CHCN 24 G</b></p>
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder</p> <p>- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>			
<p>IP65</p>			
<p>dimensions shown are not binding and may be changed without notice</p>			