

Part number

MHVN 24.32



Hood, LS-TYPE series, with 4 pegs, M32 top cable entry, size "104.27"

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 4 pegs
Size	Size 104.27
Cable entry	Top cable entry M32

Technical data

IP degree of protection IP65

Further technical details

Weight	170,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747194327
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Sub-packaging weight	0,85 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747194334

Part number MHVN 24.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "104.27" LS-TYPE version

<p>inserts: page</p> <p>CD 64 poles + @ 51+53 *</p> <p>CT, CTS **) 64 poles + @ 57 *</p> <p>CDD 108 poles + @ 64+66 *</p> <p>CDE 46 poles + @ 83+85 *</p> <p>CSH 24 poles + @ 91+93 *</p> <p>CCE 24 poles + @ 100+104 *</p> <p>CNE, CSE, JCNE, JCSE 24 poles + @ 101 and 109 *</p> <p>CSS 24 poles + @ 122+123 *</p> <p>CTE, CTSE **) 24 poles + @ 129 *</p> <p>CMSE 10+2 (aux) poles + @ 139 *</p> <p>CMCE 10+2 (aux) poles + @ 138 *</p> <p>CX 4/8 poles + @ 155 *</p> <p>MIXO 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p> housings with double lever</p>	<p> hoods with 4 pegs</p>																																			
<table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left; border-bottom: 1px solid black;">description</th> <th style="text-align: left; border-bottom: 1px solid black;">part no.</th> <th style="text-align: left; border-bottom: 1px solid black;">entry</th> <th style="text-align: left; border-bottom: 1px solid black;">part no.</th> <th style="text-align: left; border-bottom: 1px solid black;">entry</th> </tr> <tr> <td>bulkhead mounting housing, with 2 levers</td> <td>CHIN 24</td> <td>M</td> <td></td> <td></td> </tr> <tr> <td>surface mounting housing, high construction, with 2 levers</td> <td>MAPN 24.32</td> <td>32</td> <td></td> <td></td> </tr> <tr> <td>with pegs, side entry</td> <td></td> <td></td> <td>MHON 24.32</td> <td>32</td> </tr> <tr> <td>with pegs, side entry, high construction</td> <td></td> <td></td> <td>MFON 24.32</td> <td>32</td> </tr> <tr> <td>with pegs, side entry</td> <td></td> <td></td> <td>MHVN 24.32</td> <td>32</td> </tr> <tr> <td>with pegs, side entry, high construction</td> <td></td> <td></td> <td>MFVN 24.32</td> <td>32</td> </tr> </table>	description	part no.	entry	part no.	entry	bulkhead mounting housing, with 2 levers	CHIN 24	M			surface mounting housing, high construction, with 2 levers	MAPN 24.32	32			with pegs, side entry			MHON 24.32	32	with pegs, side entry, high construction			MFON 24.32	32	with pegs, side entry			MHVN 24.32	32	with pegs, side entry, high construction			MFVN 24.32	32	<p>**) only in the CHIN 24 enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	
description	part no.	entry	part no.	entry																																	
bulkhead mounting housing, with 2 levers	CHIN 24	M																																			
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32																																			
with pegs, side entry			MHON 24.32	32																																	
with pegs, side entry, high construction			MFON 24.32	32																																	
with pegs, side entry			MHVN 24.32	32																																	
with pegs, side entry, high construction			MFVN 24.32	32																																	
<p>dimensions in mm</p> <p>CHIN 24</p> <p>MAPN 24.32</p>	<p>dimensions in mm</p> <p>MFON 24.32</p> <p>MFVN 24.32</p> <p>MHON 24.32</p> <p>MHVN 24.32</p>																																				

dimensions shown are not binding and may be changed without notice