


Part number

PE 16104 PV



Mobile socket outlet, PLUSO series, 3 poles + PE, 10 h (green), 16 A, > 50 V

| Product description | | Material properties | |
|---|---|------------------------------|--|
| Product type | Socket Mobile | Colour | RAL 7035 grey, RAL 6017 green |
| Series | PE...PV, PLUSO | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| Connection type | Screw terminal connection | RoHs conformity | |
| N. of poles | 3 poles +  | China RoHs - EFUP | 50 |
| Clock position | 10 | REACH SVHC substances | Yes Lead |
| Technical data | | SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |
| Current | 16 A | Approvals / Standards | |
| Voltage | > 50 V | Reference standard | EN 60309-1 and -2 |
| IP degree of protection | IP44 | General ordering information | |
| Further technical details | | EAN13 code | 8015747062749 |
| Weight | 155,00 g | Packaging Information | |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging length | 208,00 mm |
| | | Packaging height | 140,00 mm |
| | | Packaging width | 290,00 mm |
| | | Packaging weight | 1,74 kg |
| | | Packaging volume | 8,44 dm ³ |
| | | Packaging description | Carton box |
| | | Packaging quantity | 10 Pcs |
| | | Packaging EAN code | 8015747237277 |

Part number

PE 16104 PV



Catalogue drawings

(16 / 32A) PE ... PV



| PE...PV | A | B | \varnothing min | \varnothing max | |
|-------------------------|----------------|-------|-------------------|-------------------|----|
| 16A 2P+ \oplus | 157,5 | 68 | 7 | 17 | |
| | 3P+ \oplus | 164,5 | 76 | 7 | 17 |
| | 3P+N+ \oplus | 183,5 | 83 | 9 | 22 |
| 32A 2P+ \oplus | 200,5 | 87 | 9 | 22 | |
| | 3P+ \oplus | 200,5 | 87 | 9 | 22 |
| | 3P+N+ \oplus | 200,5 | 91 | 9 | 22 |