


Part number

PE 1623 SV



Mobile plug, PLUSO series, 2 poles + PE, 2 h (green), 16 A, > 50 V, straight

Product description

Product type	Plug Mobile
Series	PE...SV, PLUSO
Connection type	Screw terminal connection
N. of poles	2 poles + 
Clock position	2
Specification	Straight

Technical data

Current	16 A
Voltage	> 50 V
IP degree of protection	IP44
Further technical details	
Weight	110,00 g
Operating temperature range (min, max)	-25°C ... +40°C

Material properties

Colour	RAL 7035 grey, RAL 6017 green
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747063272
-------------------	---------------

Packaging Information

Sub-packaging length	162,00 mm
Sub-packaging height	87,00 mm
Sub-packaging width	233,00 mm
Sub-packaging weight	1,10 kg
Sub-packaging volume	3,28 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	10 Pcs
Sub-packaging EAN barcode	8015747063289

Part number

PE 1623 SV



Catalogue drawings

(16 / 32A) PE ... SV



PE ... SV	A	B	Ø min	Ø max	
16A 2P+⊖	143,5	59	7	17	
	3P+⊖	148,5	66	7	17
	3P+N+⊖	167,5	75	9	22
32A 2P+⊖	187	80	9	22	
	3P+⊖	187	80	9	22
	3P+N+⊖	192,5	87	9	22