


Part number

# PE 1634 PP



Wall-mounting socket outlet, PLUSO series, 3 poles + PE, 3 h (red), 16 A, 380 ÷ 380 V

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Socket<br>Wall-mounting   |
| <b>Series</b>         | PE...PP, PLUSO  |
| <b>N. of poles</b>    | 3 poles +  |
| <b>Clock position</b> | 3   |

#### Technical data

|                                |                           |
|--------------------------------|---------------------------|
| <b>Current</b>                 | 16 A                      |
| <b>Voltage</b>                 | 380V (50Hz.) 440V (60Hz.) |
| <b>IP degree of protection</b> | IP44                      |

#### Further technical details

|   |                 |
|---|-----------------|
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C |
|---|-----------------|

#### Material properties

|               |                             |
|---------------|-----------------------------|
| <b>Colour</b> | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

#### Approvals / Standards

|                           |                   |
|---------------------------|-------------------|
| <b>Reference standard</b> | EN 60309-1 and -2 |
|---------------------------|-------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747154789 |
|-------------------|---------------|

Part number

# PE 1634 PP



Catalogue drawings

(16 / 32A) PE ... PP



| PE ... PP       | A  | B   | C   | D   | E  | G   | H  | X  | Y  | Pg Ø | Z Ø |
|-----------------|----|-----|-----|-----|----|-----|----|----|----|------|-----|
| <b>16A</b> 2P+⊕ | 70 | 82  | 126 | 92  | 20 | Ø22 | 16 | 53 | 65 | 16   | 4,5 |
| 3P+⊕            | 70 | 82  | 126 | 92  | 20 | Ø22 | 16 | 53 | 65 | 16   | 4,5 |
| 3P+N+⊕          | 70 | 82  | 132 | 106 | 20 | Ø22 | 16 | 53 | 65 | 16   | 4,5 |
| <b>32A</b> 2P+⊕ | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21   | 6,5 |
| 3P+⊕            | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21   | 6,5 |
| 3P+N+⊕          | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21   | 6,5 |