

Part number

PE 3264 SI



Flush-mounting plug, PLUSO series, 3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V

Product description

| | |
|-----------------------|--|
| Product type | Plug Flush-mounting |
| Series | PE...SI, PLUSO |
| N. of poles | 3 poles + |
| Clock position | 6 |
| Size | Socket fixing centre distance 77 x 85 mm |

Technical data

| | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | 380 ÷ 415 V |
| IP degree of protection | IP44 |

Further technical details

| | |
|---|-----------------|
| Weight | 226,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747067393 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|-----------------------|
| Packaging length | 330,00 mm |
| Packaging height | 175,00 mm |
| Packaging width | 295,00 mm |
| Packaging weight | 2,58 kg |
| Packaging volume | 17,04 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 10 Pcs |
| Packaging EAN code | 8015747067409 |

Part number

PE 3264 SI



Catalogue drawings

(16 / 32A) PE ... SI



| PE ... SI | A | B | C | D | E | F | G | X | Y | |
|------------|--------|----|-----|-----|-----|----|----|------|----|----|
| 16A | 2P+⊕ | 65 | 82 | 126 | 81 | 41 | 43 | 21,5 | 52 | 60 |
| | 3P+⊕ | 65 | 82 | 126 | 81 | 47 | 43 | 21,5 | 52 | 60 |
| | 3P+N+⊕ | 90 | 100 | 146 | 93 | 54 | 60 | 27,5 | 77 | 85 |
| 32A | 2P+⊕ | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 77 | 85 |
| | 3P+⊕ | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 77 | 85 |
| | 3P+N+⊕ | 90 | 100 | 160 | 106 | 62 | 60 | 27,5 | 77 | 85 |