


Part number

# PE 3294 PV



Mobile socket outlet, PLUSO series, 3 poles + PE, 9 h (blue), 32 A, 200 ÷ 250 V

| Product description                           |   | Material properties          |   |
|---|---|------------------------------|---|
| <b>Product type</b>                           | Socket<br>Mobile  | <b>Colour</b>                | RAL 7035 grey, RAL 5015 blue  |
| <b>Series</b>                                 | PE...PV, PLUSO  | <b>RoHs conformity</b>       | Compliant with exemption<br>6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                            | 3 poles +  | <b>China RoHs - EFUP</b>     | 50  |
| <b>Clock position</b>                         | 9   | <b>REACH SVHC substances</b> | Yes<br>Lead   |
| Technical data                                |   | <b>SCIP number</b>           | Ca7de37f-add8-4b77-9861-279c94903ade  |
| <b>Current</b>                                | 32 A  | Approvals / Standards        |   |
| <b>Voltage</b>                                | 200 ÷ 250 V   | <b>Reference standard</b>    | EN 60309-1 and -2   |
| <b>IP degree of protection</b>                | IP44  | General ordering information |   |
| Further technical details                     |   | <b>EAN13 code</b>            | 8015747068130   |
| <b>Weight</b>                                 | 230,00 g  | Packaging Information        |   |
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C   | <b>Packaging length</b>      | 330,00 mm   |
|   |   | <b>Packaging height</b>      | 175,00 mm   |
|   |   | <b>Packaging width</b>       | 295,00 mm   |
|   |   | <b>Packaging weight</b>      | 2,62 kg   |
|   |   | <b>Packaging volume</b>      | 17,04 dm <sup>3</sup>   |
|   |   | <b>Packaging description</b> | Carton box  |
|   |   | <b>Packaging quantity</b>    | 10 Pcs  |
|   |   | <b>Packaging EAN code</b>    | 8015747068147   |


Part number

# PE 3294 PV



Catalogue drawings

(16 / 32A) PE ... PV



| PE...PV         | A      | B     | Ø min | Ø max |    |
|-----------------|--------|-------|-------|-------|----|
| <b>16A</b> 2P+⊕ | 157,5  | 68    | 7     | 17    |    |
|                 | 3P+⊕   | 164,5 | 76    | 7     | 17 |
|                 | 3P+N+⊕ | 183,5 | 83    | 9     | 22 |
| <b>32A</b> 2P+⊕ | 200,5  | 87    | 9     | 22    |    |
|                 | 3P+⊕   | 200,5 | 87    | 9     | 22 |
|                 | 3P+N+⊕ | 200,5 | 91    | 9     | 22 |