


Part number

PEW 1665 PV



Mobile socket outlet, PLUSO series, 3 poles + N + PE, 6 h (red), 16 A, 380 ÷ 415 V

Product description		Material properties	
Product type	Socket Mobile	Colour	RAL 7035 grey, RAL 3000 red
Series	PEW...PV, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	China RoHs - EFUP	50
N. of poles	3 poles + N + 	REACH SVHC substances	Yes Lead
Clock position	6	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Technical data		Approvals / Standards	
Current	16 A	Reference standard	EN 60309-1 and -2
Voltage	380 ÷ 415 V	General ordering information	
IP degree of protection	IP67	EAN13 code	8015747073035
Further technical details		Packaging Information	
Weight	260,00 g	Packaging length	255,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging height	195,00 mm
		Packaging width	245,00 mm
		Packaging weight	2,75 kg
		Packaging volume	12,18 dm ³
		Packaging description	Carton box
		Packaging quantity	10 Pcs
		Packaging EAN code	8015747073042


Part number

PEW 1665 PV



Catalogue drawings

(16 / 32A) PEW ... PV



PEW...PV	A	B	ø min	ø max
16A 2P+⊖	145	77	7	16
3P+⊖	145	85	7	16
3P+N+⊖	145	93	8	24
32A 2P+⊖	162	97	8	24
3P+⊖	162	97	8	24
3P+N+⊖	162	105	8	24