

Part number

# PK 12574 PB5



Interlocked switched socket-outlet, PK series,  
3 poles + PE, 7 h (black), 125 A, 480 ÷ 500 V,  
NH00 fuse carrier

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7035 grey, RAL 9005 black
<b>Series</b>	PK..PB5		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles +	<b>RoHs conformity</b>	50
<b>Clock position</b>	7	<b>China RoHs - EFUP</b>	50
<b>Specification</b>	NH00 fuse carrier	<b>REACH SVHC substances</b>	Yes Lead
Technical data		<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
<b>Current</b>	125 A	<b>Approvals / Standards</b>	
<b>Voltage</b>	480 ÷ 500 V	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>IP degree of protection</b>	IP55	General ordering information	
Further technical details		<b>EAN13 code</b>	8015747079488
<b>Weight</b>	9.000,00 g	Packaging Information	
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging length</b>	570,00 mm
<b>IK rating (impact degree of protection)</b>	IK10	<b>Packaging height</b>	200,00 mm
		<b>Packaging width</b>	265,00 mm
		<b>Packaging weight</b>	9,70 kg
		<b>Packaging volume</b>	30,21 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	1 Pcs
		<b>Packaging EAN code</b>	8015747079495
		<b>Sub-packaging length</b>	113,00 mm
		<b>Sub-packaging height</b>	36,00 mm
		<b>Sub-packaging width</b>	180,00 mm
		<b>Sub-packaging volume</b>	0,73 dm <sup>3</sup>

Part number

# PK 12574 PB5



## Catalogue drawings

