

Part number

PK 3225 EB



Interlocked switched socket-outlet, PK series, 3 poles + N + PE, 2 h (green), 32 A, > 50 V, without fuse-carrier

Product description

Product type	Interlocked switched socket-outlet
Series	PK..EB
N. of poles	3 poles + N +
Clock position	2
Cable entry	Pg29
Specification	Without fuse-carrier

Technical data

Current	32 A
Voltage	> 50 V
IP degree of protection	IP44

Further technical details

Weight	1.330,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7035 grey
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747081023
-------------------	---------------

Packaging Information

Sub-packaging length	290,00 mm
Sub-packaging height	125,00 mm
Sub-packaging width	155,00 mm
Sub-packaging weight	1,33 kg
Sub-packaging volume	5,62 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747081030

Part number

PK 3225 EB



Catalogue drawings

