


Part number

PK 6344 EB



Interlocked switched socket-outlet, PK series,
3 poles + PE, 4 h (yellow), 63 A, 100 ÷ 130 V,
without fuse-carrier

Product description	
Product type	Interlocked switched socket-outlet
Series	PK..EB
N. of poles	3 poles + 
Clock position	4
Size	114x228 fixing plates FC xx41 TB
Cable entry	Pg29
Specification	Without fuse-carrier
Technical data	
Current	63 A
Voltage	100 ÷ 130 V
IP degree of protection	IP44
Further technical details	
Weight	1.800,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7035 grey, RAL 1021 yellow
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747082259
Packaging Information	
Sub-packaging length	290,00 mm
Sub-packaging height	125,00 mm
Sub-packaging width	155,00 mm
Sub-packaging weight	1,80 kg
Sub-packaging volume	5,62 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747082266

Part number

PK 6344 EB



Catalogue drawings

