

Part number

RC2D 0.7 AN



Male crimp contact, RC series, 16 A, gold plated, wire cross section 0,75 mm², AWG 18, advanced opening, HNM - High Number of Matings version

Product description

| | |
|----------------------|----------------------------------------------------------|
| Product type | Crimp contact |
| Series | RC |
| Gender | Male |
| Specification | HNM - High Number of Matings version Advanced opening |

Technical data

| | |
|---------------------------|----------------------|
| Current | 16 A |
| Wire cross-section | 0,75 mm ² |
| AWG size | 18 |
| Contact type | Turned gold plated |

Material properties

| | |
|------------------------------|--------------------------------------------------------------------------------|
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | C0979fba-9907-458f-a94a-db781440f273 |

Approvals / Standards

| | |
|-----------|-------|
| UL | ECBT2 |
|-----------|-------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747180672 |
|-------------------|---------------|

Packaging Information


| | |
|----------------------------------|----------------------|
| Sub-packaging length | 50,00 mm |
| Sub-packaging height | 44,00 mm |
| Sub-packaging width | 50,00 mm |
| Sub-packaging volume | 0,11 dm ³ |
| Sub-packaging description | Plastic box |
| Sub-packaging quantity | 50 Pcs |
| Sub-packaging EAN barcode | 8015747180689 |

Part number

RC2D 0.7 AN



Catalogue drawings



RCD2..AN contacts

| conductor section mm ² | conductor slot $\varnothing A$ (mm) | conductors stripping length (mm) |
|--------------------------------------|----------------------------------------|-------------------------------------|
| 0,5 | 1,1 | 7,5 |
| 0,75 | 1,3 | 7,5 |
| 1,0 | 1,45 | 7,5 |
| 1,5 | 1,8 | 7,5 |
| 2,5 | 2,2 | 7,5 |