

Part number

SIP 1665 SV



Mobile plug, PLUSO series, 3 poles + N + PE, 6 h (red), 16 A, 200/346 ÷ 240/415 V, with phase inverter

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7035 grey, RAL 3000 red
Series	SIP...SV, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	China RoHs - EFUP	50
N. of poles	3 poles + N + 	REACH SVHC substances	Yes Lead
Clock position	6	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Specification	With phase inverter	Approvals / Standards	
Technical data		Reference standard	EN 60309-1 and -2
Current	16 A	General ordering information	
Voltage	200/346 ÷ 240/415 V	EAN13 code	8015747083898
IP degree of protection	IP44	Packaging Information	
Further technical details		Packaging length	208,00 mm
Weight	169,00 g	Packaging height	140,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging width	290,00 mm
		Packaging weight	1,87 kg
		Packaging volume	8,44 dm³
		Packaging description	Carton box
		Packaging quantity	10 Pcs
		Packaging EAN code	8015747034531


Part number

SIP 1665 SV



Catalogue drawings

SIP ... SV




	A	B	Ø min	Ø min
16A	167,5	75	9	22
32A	192,5	87	9	22

Catalogue drawings



SIPW ... SV



	A	B
16A	150	86
32A	175	99,5
