


Part number

SQV 32115.5



Interlocked switched socket-outlet, SQV series, 3 poles + N + PE, 11 h (red), 32 A, 250/440 ÷ 265/460 V, sectionable fuse carrier 10 x 38 mm

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | SQV |
| N. of poles | 3 poles + N +  |
| Clock position | 11 |
| Specification | Sectionable fuse carrier 10 x 38 mm |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 32 A |
| Voltage | 250/440V ÷ 265/460V |
| IP degree of protection | IP55 |

Further technical details

| | |
|--|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK08 |

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747160322 |
|-------------------|---------------|

Part number

SQV 32115.5



Catalogue drawings



Catalogue drawings



| SQV.5 | | A |
|-------|--------|-----|
| 32A | 2P+⊕ | 92 |
| | 3P+⊕ | 92 |
| | 3P+N+⊕ | 100 |