


Part number

# TM 1635 SIS



Interlocked switched socket-outlet, TM series,  
3 poles + N + PE, 3 h (red), 16 A, 380 ÷ 380  
V, sectionable fuse carrier 10 x 38 mm,  
without base box

## Product description

<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	TM.. SIS/KSIS
<b>N. of poles</b>	3 poles + N + 
<b>Clock position</b>	3
<b>Specification</b>	Sectionable fuse carrier 10 x 38 mm Without base box

## Technical data

<b>Current</b>	16 A
<b>Voltage</b>	380V (50Hz.) 440V (60Hz.)
<b>IP degree of protection</b>	IP66 / IP67

## Further technical details

<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>UL 94 flammability rating</b>	V-2
<b>IK rating (impact degree of protection)</b>	IK10

## Material properties

<b>Colour</b>	RAL 7012 grey, RAL 3000 red
---------------	-----------------------------

## Approvals / Standards

<b>Reference standard</b>	EN 60309-1, -2 e -4
---------------------------	---------------------

## General ordering information


<b>EAN13 code</b>	8015747161442
-------------------	---------------

Part number

# TM 1635 SIS



Catalogue drawings



	<b>A</b>	<b>B</b>
<b>2P+⊕</b>	83	276
<b>3P+⊕</b>	85	276
<b>3P+N+⊕</b>	90	277