

Part number

# TM 1674 SIS



Interlocked switched socket-outlet, TM series, 3 poles + PE, 7 h (black), 16 A, 480 ÷ 500 V, sectionable fuse carrier 10 x 38 mm, without base box

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7012 grey, RAL 9005 black
<b>Series</b>	TM.. SIS/KSIS		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles +	<b>RoHs conformity</b>	
<b>Clock position</b>	7	<b>China RoHs - EFUP</b>	50
<b>Specification</b>	Sectionable fuse carrier 10 x 38 mm Without base box	<b>REACH SVHC substances</b>	Yes Lead
Technical data		<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
<b>Current</b>	16 A	<b>Approvals / Standards</b>	
<b>Voltage</b>	480 ÷ 500 V	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>IP degree of protection</b>	IP66 / IP67	General ordering information	
Further technical details		<b>EAN13 code</b>	8015747090339
<b>Weight</b>	1.170,00 g	Packaging Information	
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging weight</b>	11,52 kg
<b>UL 94 flammability rating</b>	V-2	<b>Packaging volume</b>	52,36 dm <sup>3</sup>
<b>IK rating (impact degree of protection)</b>	IK10	<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	9 Pcs
		<b>Packaging EAN code</b>	8015747128926
		<b>Sub-packaging length</b>	95,00 mm
		<b>Sub-packaging height</b>	40,00 mm
		<b>Sub-packaging width</b>	253,00 mm
		<b>Sub-packaging weight</b>	1,28 kg
		<b>Sub-packaging volume</b>	0,96 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Carton tray
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747108461

Part number

# TM 1674 SIS



Catalogue drawings



	<b>A</b>	<b>B</b>
<b>2P+⊕</b>	83	276
<b>3P+⊕</b>	85	276
<b>3P+N+⊕</b>	90	277