

Part number

TM 2656 DT



Assembled modular base, TM series,
composed of 1 TM 1145 TB and 1 TM 1456 TB
back plates and 1 TM 2614 GB box

| Product description | |
|--|--|
| Product type | Assembled modular base |
| Series | TM |
| Specification | Composed of 1 TM 1145 TB and 1 TM 1456 TB back plates and 1 TM 2614 GB box |
| Technical data | |
| IP degree of protection | IP66 / IP67 |
| Further technical details | |
| Weight | 2.060,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|----------------------------------|--|
| Colour | RAL 7012 grey |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | B0214dad-d2d9-4e91-a5b4-f4c9b4612083 |
| General ordering information | |
| EAN13 code | 8015747096539 |
| Packaging Information | |
| Packaging length | 630,00 mm |
| Packaging height | 300,00 mm |
| Packaging width | 280,00 mm |
| Packaging weight | 4,12 kg |
| Packaging volume | 52,92 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 2 Pcs |
| Packaging EAN code | 8015747111348 |
| Sub-packaging weight | 2,06 kg |
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747116107 |

Part number

TM 2656 DT



Catalogue drawings

