


Part number

# TM 32104KSP



Interlocked switched socket-outlet, TM series,  
3 poles + PE, 10 h (green), 32 A, > 50 V,  
without fuse-carrier, with base box

| Product description                                |   | Material properties                  |  |
|--|---|--------------------------------------|--|
| <b>Product type</b>                                | Interlocked switched socket-outlet  | <b>Colour</b>                        | RAL 7012 grey, RAL 6017 green  |
| <b>Series</b>                                      | TM..SP/KSP  |                                      | Compliant with exemption<br>6(c): copper alloy containing up to 4% lead by<br>weight |
| <b>N. of poles</b>                                 | 3 poles +  | <b>RoHs conformity</b>               | 6(c): copper alloy containing up to 4% lead by<br>weight                             |
| <b>Clock position</b>                              | 10  | <b>China RoHs - EFUP</b>             | 50   |
| <b>Specification</b>                               | Without fuse-carrier<br>With base box   | <b>REACH SVHC substances</b>         | Yes<br>Lead  |
| Technical data                                     |   | <b>SCIP number</b>                   | Ce861c8d-b979-403b-96d9-80aef6dc281d   |
| <b>Current</b>                                     | 32 A  | Approvals / Standards                |  |
| <b>Voltage</b>                                     | > 50 V  | <b>Reference standard</b>            | EN 60309-1, -2 e -4  |
| <b>IP degree of protection</b>                     | IP66 / IP67   | General ordering information         |  |
| Further technical details                          |   | <b>EAN13 code</b>                    | 8015747161909  |
| <b>Weight</b>                                      | 1.380,00 g  | Packaging Information                |  |
| <b>Operating temperature<br/>range (min, max)</b>  | -25°C ... +40°C   | <b>Packaging length</b>              | 385,00 mm  |
| <b>UL 94 flammability rating</b>                   | V-2   | <b>Packaging height</b>              | 320,00 mm  |
| <b>IK rating (impact degree of<br/>protection)</b> | IK10  | <b>Packaging width</b>               | 485,00 mm  |
|  |   | <b>Packaging weight</b>              | 12,52 kg   |
|  |   | <b>Packaging volume</b>              | 59,75 dm <sup>3</sup>  |
|  |   | <b>Packaging description</b>         | Carton box   |
|  |   | <b>Packaging quantity</b>            | 9 Pcs  |
|  |   | <b>Packaging EAN code</b>            | 8015747275781  |
|  |   | <b>Sub-packaging weight</b>          | 1,39 kg  |
|  |   | <b>Sub-packaging description</b>     | Carton tray  |
|  |   | <b>Sub-packaging quantity</b>        | 1 Pcs  |
|  |   | <b>Sub-packaging EAN<br/>barcode</b> | 8015747275774  |

Part number

# TM 32104KSP



Catalogue drawings



|               | A   | B   |
|---------------|-----|-----|
| <b>2P+⊕</b>   | 133 | 276 |
| <b>3P+⊕</b>   | 135 | 276 |
| <b>3P+N+⊕</b> | 140 | 277 |