


Part number

TM 32114KIR



Interlocked switched socket-outlet, TM series, 3 poles + PE, 11 h (red), 32 A, 440 ÷ 460 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..IR/KIR |
| N. of poles | 3 poles +  |
| Clock position | 11 |
| Specification | With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box |

Technical data

| | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | 440 ÷ 460 V |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|--|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7012 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747161978 |
|-------------------|---------------|

Part number

TM 32114KIR



Catalogue drawings



| | A | B |
|--------|-----|-----|
| 2P+⊕ | 133 | 276 |
| 3P+⊕ | 135 | 276 |
| 3P+N+⊕ | 140 | 277 |