


Part number

# TM 3234 SP



Interlocked switched socket-outlet, TM series,  
3 poles + PE, 3 h (red), 32 A, 380 ÷ 380 V,  
with base box

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | TM..SP/KSP  |
| <b>N. of poles</b>    | 3 poles +  |
| <b>Clock position</b> | 3   |
| <b>Specification</b>  | With base box   |

#### Technical data

|                                |                           |
|--------------------------------|---------------------------|
| <b>Current</b>                 | 32 A                      |
| <b>Voltage</b>                 | 380V (50Hz.) 440V (60Hz.) |
| <b>IP degree of protection</b> | IP66 / IP67               |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>UL 94 flammability rating</b>               | V-2             |
| <b>IK rating (impact degree of protection)</b> | IK10            |

#### Material properties

|               |                             |
|---------------|-----------------------------|
| <b>Colour</b> | RAL 7012 grey, RAL 3000 red |
|---------------|-----------------------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747162784 |
|-------------------|---------------|

Part number

# TM 3234 SP



Catalogue drawings



|               | <b>A</b> |
|---------------|----------|
| <b>2P+⊕</b>   | 162      |
| <b>3P+⊕</b>   | 162      |
| <b>3P+N+⊕</b> | 169      |