


Part number

# TM 3234KSP



Interlocked switched socket-outlet, TM series,  
3 poles + PE, 3 h (red), 32 A, 380 ÷ 380 V,  
without fuse-carrier, with base box

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7012 grey, RAL 3000 red
<b>Series</b>	TM..SP/KSP		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles + 	<b>RoHs conformity</b>	50
<b>Clock position</b>	3	<b>China RoHs - EFUP</b>	50
<b>Specification</b>	Without fuse-carrier With base box	<b>REACH SVHC substances</b>	Yes Lead
Technical data		<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
<b>Current</b>	32 A	Approvals / Standards	
<b>Voltage</b>	380V (50Hz.) 440V (60Hz.)	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>IP degree of protection</b>	IP66 / IP67	General ordering information	
Further technical details		<b>EAN13 code</b>	8015747137188
<b>Weight</b>	1.400,00 g	Packaging Information	
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging length</b>	385,00 mm
<b>UL 94 flammability rating</b>	V-2	<b>Packaging height</b>	320,00 mm
<b>IK rating (impact degree of protection)</b>	IK10	<b>Packaging width</b>	485,00 mm
		<b>Packaging weight</b>	12,60 kg
		<b>Packaging volume</b>	59,75 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	9 Pcs
		<b>Packaging EAN code</b>	8015747137249
		<b>Sub-packaging weight</b>	1,40 kg
		<b>Sub-packaging description</b>	Carton tray
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747137256

Part number

# TM 3234KSP



Catalogue drawings



	A	B
<b>2P+⊕</b>	133	276
<b>3P+⊕</b>	135	276
<b>3P+N+⊕</b>	140	277