


Part number

TM 3235 IR



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 3 h (red), 32 A, 380 ÷ 380 V, with compartment for modular units, 6 DIN-rail modules EN 60715, with base box

| Product description | |
|---|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..IR/KIR |
| N. of poles | 3 poles + N +  |
| Clock position | 3 |
| Specification | With compartment for modular units, 6 DIN-rail modules EN 60715 With base box |
| Technical data | |
| Current | 32 A |
| Voltage | 380V (50Hz.) 440V (60Hz.) |
| IP degree of protection | IP66 / IP67 |
| Further technical details | |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|------------------------------|-----------------------------|
| Colour | RAL 7012 grey, RAL 3000 red |
| Approvals / Standards | |
| Reference standard | EN 60309-1, -2 e -4 |
| General ordering information | |
| EAN13 code | 8015747162876 |

Part number

TM 3235 IR



Catalogue drawings



| | A |
|---------------|----------|
| 2P+⊕ | 162 |
| 3P+⊕ | 162 |
| 3P+N+⊕ | 169 |