


Part number

# TM 3265 IS



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 6 h (red), 32 A, 200/346 ÷ 240/415 V, sectionable fuse carrier 14 x 51 mm, with base box

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7012 grey, RAL 3000 red
<b>Series</b>	TM.. IS/KIS		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles + N + 	<b>RoHs conformity</b>	6(c): copper alloy containing up to 4% lead by weight
<b>Clock position</b>	6	<b>China RoHs - EFUP</b>	50
<b>Size</b>	145 x 565 x 18 mm	<b>REACH SVHC substances</b>	Yes Lead
<b>Specification</b>	Sectionable fuse carrier 14 x 51 mm With base box	<b>SCIP number</b>	F6799547-ab84-42f2-938f-233ba663766d
Technical data		Approvals / Standards	
<b>Current</b>	32 A	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>Voltage</b>	200/346 ÷ 240/415 V	General ordering information	
<b>IP degree of protection</b>	IP66 / IP67	<b>EAN13 code</b>	8015747092036
Further technical details		Packaging Information	
<b>Weight</b>	3.325,00 g	<b>Sub-packaging length</b>	150,00 mm
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Sub-packaging height</b>	188,00 mm
<b>UL 94 flammability rating</b>	V-2	<b>Sub-packaging width</b>	430,00 mm
<b>IK rating (impact degree of protection)</b>	IK10	<b>Sub-packaging weight</b>	3,33 kg
		<b>Sub-packaging volume</b>	12,13 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Carton box
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747092050

Part number

# TM 3265 IS



Catalogue drawings



	<b>A</b>
<b>2P+⊕</b>	162
<b>3P+⊕</b>	162
<b>3P+N+⊕</b>	169