

Part number

TM 3275 IT



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 7 h (black), 32 A, 277/480 ÷ 288/500 V, E33 - DIII fuse carrier, with base box



Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 9005 black
Series	TM.. IT		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + N + 	RoHs conformity	
Clock position	7	China RoHs - EFUP	50
Specification	E33 - DIII fuse carrier With base box	REACH SVHC substances	Yes Lead
Technical data		SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Current	32 A	Approvals / Standards	
Voltage	277/480 ÷ 288/500 V	Reference standard	EN 60309-1, -2 e -4
IP degree of protection	IP66 / IP67	General ordering information	
Further technical details		EAN13 code	8015747092142
Weight	3.520,00 g	Packaging Information	
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging length	150,00 mm
UL 94 flammability rating	V-2	Sub-packaging height	188,00 mm
IK rating (impact degree of protection)	IK10	Sub-packaging width	430,00 mm
		Sub-packaging weight	3,52 kg
		Sub-packaging volume	12,13 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747107556

Part number

TM 3275 IT



Catalogue drawings



	A
2P+⊕	162
3P+⊕	162
3P+N+⊕	169