


Part number

# TM 3294KSP



Interlocked switched socket-outlet, TM series,  
3 poles + PE, 9 h (blue), 32 A, 200 ÷ 250 V,  
without fuse-carrier, with base box

| Product description                            |   |
|--|---|
| <b>Product type</b>                            | Interlocked switched socket-outlet  |
| <b>Series</b>                                  | TM..SP/KSP  |
| <b>N. of poles</b>                             | 3 poles +  |
| <b>Clock position</b>                          | 9   |
| <b>Size</b>                                    | 115 x 450 x 18 mm   |
| <b>Specification</b>                           | Without fuse-carrier<br>With base box   |
| Technical data                                 |   |
| <b>Current</b>                                 | 32 A  |
| <b>Voltage</b>                                 | 200 ÷ 250 V   |
| <b>IP degree of protection</b>                 | IP66 / IP67   |
| Further technical details                      |   |
| <b>Weight</b>                                  | 1.400,00 g  |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   |
| <b>UL 94 flammability rating</b>               | V-2   |
| <b>IK rating (impact degree of protection)</b> | IK10  |

| Material properties          |                              |
|------------------------------|------------------------------|
| <b>Colour</b>                | RAL 7012 grey, RAL 5015 blue |
| Approvals / Standards        |                              |
| <b>Reference standard</b>    | EN 60309-1, -2 e -4          |
| General ordering information |                              |
| <b>EAN13 code</b>            | 8015747126281                |

Part number

# TM 3294KSP



Catalogue drawings



|                | A   | B   |
|----------------|-----|-----|
| 2P+ $\oplus$   | 133 | 276 |
| 3P+ $\oplus$   | 135 | 276 |
| 3P+N+ $\oplus$ | 140 | 277 |