


Part number

# TM 6363 SIS



Interlocked switched socket-outlet, TM series, 2 poles + PE, 6 h (blue), 63 A, 200 ÷ 250 V, sectionable fuse carrier 22 x 58 mm, without base box

| Product description                            |   | Material properties              |  |
|--|---|----------------------------------|--|
| <b>Product type</b>                            | Interlocked switched socket-outlet  | <b>Colour</b>                    | RAL 7012 grey, RAL 5015 blue   |
| <b>Series</b>                                  | TM.. SIS/KSIS   |                                  | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                             | 2 poles +  | <b>RoHs conformity</b>           |  |
| <b>Clock position</b>                          | 6   | <b>China RoHs - EFUP</b>         | 50   |
| <b>Size</b>                                    | 144 x 370 mm fixing distance, for assembly in single boxes                                  | <b>REACH SVHC substances</b>     | Yes<br>Lead  |
| <b>Specification</b>                           | Sectionable fuse carrier 22 x 58 mm<br>Without base box                                     | <b>SCIP number</b>               | F6799547-ab84-42f2-938f-233ba663766d   |
| Technical data                                 |   | Approvals / Standards            |  |
| <b>Current</b>                                 | 63 A  | <b>Reference standard</b>        | EN 60309-1, -2 e -4  |
| <b>Voltage</b>                                 | 200 ÷ 250 V   | General ordering information     |  |
| <b>IP degree of protection</b>                 | IP66 / IP67   | <b>EAN13 code</b>                | 8015747214780  |
| Further technical details                      |   | Packaging Information            |  |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   | <b>Sub-packaging length</b>      | 150,00 mm  |
| <b>UL 94 flammability rating</b>               | V-0 (insert), V-2 (enclosure)   | <b>Sub-packaging height</b>      | 188,00 mm  |
| <b>IK rating (impact degree of protection)</b> | IK10  | <b>Sub-packaging width</b>       | 430,00 mm  |
|  |   | <b>Sub-packaging volume</b>      | 12,13 dm <sup>3</sup>  |
|  |   | <b>Sub-packaging description</b> | Carton box   |
|  |   | <b>Sub-packaging quantity</b>    | 1 Pcs  |
|  |   | <b>Sub-packaging EAN barcode</b> | 8015747012133  |