


Part number

# TM 6364 SPX



Interlocked switched socket-outlet, TM ATEX series, 3 poles + PE, 6 h (red), 63 A, 380 ÷ 415 V, sectionable fuse carrier 22 x 58 mm, with base box

## Product description

<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	TM ATEX
<b>N. of poles</b>	3 poles + 
<b>Clock position</b>	6
<b>Size</b>	144 x 370 mm fixing distance, for assembly in plates TM xx56 TB
<b>Specification</b>	Sectionable fuse carrier 22 x 58 mm With base box

## Technical data

<b>Current</b>	63 A
<b>Voltage</b>	380 ÷ 415 V
<b>IP degree of protection</b>	IP66 / IP67

## Further technical details

<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>IK rating (impact degree of protection)</b>	IK10

## Material properties

<b>Colour</b>	RAL 7012 grey, RAL 3000 red
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	F6799547-ab84-42f2-938f-233ba663766d

## Approvals / Standards

<b>Reference standard</b>	EN 60309-1, -2 e -4
---------------------------	---------------------

## General ordering information

<b>EAN13 code</b>	8015747179980
-------------------	---------------

## Packaging Information

<b>Sub-packaging length</b>	150,00 mm
<b>Sub-packaging height</b>	188,00 mm
<b>Sub-packaging width</b>	430,00 mm
<b>Sub-packaging volume</b>	12,13 dm <sup>3</sup>
<b>Sub-packaging description</b>	Carton box
<b>Sub-packaging quantity</b>	1 Pcs
<b>Sub-packaging EAN barcode</b>	8015747210560