


Part number

# CQF 17



Female insert, CQ series, crimp connection, 17 poles + PE, 10 A 160 V 2.5 kV 3, size "32.13"


Product description		Material properties	
<b>Product type</b>	Insert	<b>Main material</b>	Polycarbonate (PC)
<b>Series</b>	CQ	<b>Colour</b>	RAL 7032 grey
<b>Connection type</b>	Crimp connection	<b>RoHs conformity</b>	Compliant
<b>Gender</b>	Female	<b>China RoHs - EFUP</b>	E
<b>N. of poles</b>	17 poles + 	<b>REACH SVHC substances</b>	No
<b>Size</b>	Size "32.13"	<b>Approvals / Standards</b>	
<b>Technical data</b>		<b>Certifications</b>	DNV, BV, EAC
<b>Current</b>	10 A	<b>UL</b>	ECBT2
<b>Voltage</b>	160 V	<b>cUL</b>	ECBT8
<b>Rated impulse withstand voltage</b>	2,5 kV	<b>General ordering information</b>	
<b>Pollution degree</b>	3	<b>EAN13 code</b>	8015747232777
<b>Rated voltage according to UL/CSA</b>	250 V	<b>eCl@ss 8.1</b>	27440205
<b>IP degree of protection</b>	IP20 without enclosure, IP66/IP67/IP69 with enclosure	<b>ETIM 7.0</b>	EC000438
<b>Further technical details</b>		<b>Packaging Information</b>	
<b>Characteristics according to EN 61984</b>	10A 160V 2,5kV 3; 10A 250V 4kV 2	<b>Packaging length</b>	245,00 mm
<b>Mating cycles</b>	≥ 500	<b>Packaging height</b>	165,00 mm
<b>Insulation resistance</b>	≥ 10 GΩ	<b>Packaging width</b>	215,00 mm
<b>Contact resistance</b>	≤ 3 mΩ	<b>Packaging weight</b>	0,88 kg
<b>Weight</b>	13,77 g	<b>Packaging volume</b>	8,69 dm <sup>3</sup>
<b>Operating temperature range (min, max)</b>	-40 °C ... +125 °C	<b>Packaging description</b>	Carton box
<b>UL 94 flammability rating</b>	V-0	<b>Packaging quantity</b>	50 Pcs
		<b>Packaging EAN code</b>	8015747233644
		<b>Sub-packaging weight</b>	0,02 kg
		<b>Sub-packaging description</b>	Plastic bag
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747300315

Part number


# CQF 17



## Catalogue drawings



## Derating curves



Notes