

Part number

CX 01 YF



Female modular insert, Mixo series, crimp connection, 1 pole, 2 modules, 200 A 1000 V 8 kV 3





Product description		Material properties	
Product type	Modular insert	Main material	Polycarbonate
Series	Mixo	Colour	RAL 7032 grey
Connection type	Crimp connection	RoHs conformity	Compliant
Gender	Female	China RoHs - EFUP	E
N. of poles	1 pole	REACH SVHC substances	No
Size	2 modules	Approvals / Standards	
Technical data		Reference standard	EN 61984:2009-06
Current	200 A	Certifications	CSA, CQC, DNV, BV, EAC
Voltage	1000 V	UL	ECBT2
Rated impulse withstand voltage	8 kV	cUL	ECBT8
Pollution degree	3	General ordering information	
Rated voltage according to UL/CSA	600 V	EAN13 code	8015747168052
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	eCl@ss 8.1	27440205
Further technical details		ETIM 7.0	EC000438
Characteristics according to EN 61984	200A 1000V 8kV 3; 200A 920/1600V 8kV 2	Packaging Information	
Insulation resistance	≥ 10 GΩ	Packaging length	112,00 mm
Contact resistance	≤ 0,2 mΩ	Packaging height	95,00 mm
Weight	32,00 g	Packaging width	117,00 mm
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging weight	0,21 kg
UL 94 flammability rating	V-0	Packaging volume	1,24 dm ³
		Packaging description	Carton box
		Packaging quantity	5 Pcs
		Packaging EAN code	8015747168366
		Sub-packaging weight	0,04 kg
		Sub-packaging description	Plastic bag
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747168373

Part number

CX 01 YF



Catalogue drawings



Notes