

Part number

CX 02 HF



Female modular insert, Mixo series, crimp connection, 2 poles, 2 modules, 16 A 2900/5000 V 15 kV 3, with heat-shrinking tube

Product description

Product type	Modular insert
Series	Mixo
Connection type	Crimp connection
Gender	Female
N. of poles	2 poles
Size	2 modules
Specification	With heat-shrinking tube

Technical data

Current	16 A
Voltage	2900 - 5000 V
Rated impulse withstand voltage	15 kV
Pollution degree	3
Rated voltage according to UL/CSA	600V
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure

Further technical details

Characteristics according to EN 61984	16A 2900/5000V 15kV 3
Insulation resistance	$\geq 10 \text{ G}\Omega$
Contact resistance	$\leq 1 \text{ m}\Omega$
Weight	53,00 g
Operating temperature range (min, max)	-40 °C ... +125 °C
UL 94 flammability rating	V-0

Material properties

Main material	Polycarbonate
Colour	RAL 7032 grey
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Reference standard	EN 61984:2009-06
Certifications	DNV

General ordering information

EAN13 code	8015747150385
eCl@ss 8.1	27440205
ETIM 7.0	EC000438

Packaging Information

Sub-packaging weight	0,05 kg
Sub-packaging description	Plastic bag
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747167895



Part number

CX 02 HF




Catalogue drawings

CX 02 HM



CX 02 HM



Notes