

Part number
JKSM 04



Male insert, JKS series, spring terminal connection, 4 poles + PE, 10 A 400 V 4 kV 3, size "21.21"

Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	JKS	Other materials	Contacts: copper alloy Gasket: NBR
Connection type	Spring terminal connection	Colour	RAL 7035 grey
Gender	Male	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	4 poles +	China RoHs - EFUP	50
Size	Size "21.21"	REACH SVHC substances	Yes Lead
Technical data		SCIP number	1a9c93ff-0445-4a16-81e3-1609ac5274d6
Current	10 A	Approvals / Standards	
Voltage	400 V	Reference standard	EN 61984:2009-06
Rated impulse withstand voltage	4 kV	Certifications	CSA, CQC, DNV, BV, EAC
Pollution degree	3	UL	ECBT2
Rated voltage according to UL/CSA	600V	cUL	ECBT8
Wire cross-section	0,14 mm ² - 2,50 mm ²	General ordering information	
AWG size	26 - 14	EAN13 code	8015747202244
Contact type	Turned tin plated	Packaging Information	
IP degree of protection	IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure	Packaging length	210,00 mm
Further technical details		Packaging height	200,00 mm
Characteristics according to EN 61984	10A 400V 4kV 3; 10A 690V 4kV 2	Packaging width	130,00 mm
Mating cycles	≥ 200	Packaging weight	3,10 kg
Insulation resistance	≥ 10 GΩ	Packaging volume	5,46 dm ³
Weight	15,00 g	Packaging description	Carton box
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging quantity	200 Pcs
UL 94 flammability rating	V-0	Packaging EAN code	8015747202251
		Sub-packaging length	197,00 mm
		Sub-packaging height	35,00 mm
		Sub-packaging width	124,00 mm
		Sub-packaging weight	0,62 kg
		Sub-packaging volume	0,85 dm ³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	40 Pcs
		Sub-packaging EAN barcode	8015747202268

Part number

JKSM 04



Notes

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.