

Part number

# MHVN 24.32



Hood, LS-TYPE series, with 4 pegs, M32 top cable entry, size "104.27"

#### Product description

<b>Product type</b>	Hood
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 4 pegs
<b>Size</b>	Size 104.27
<b>Cable entry</b>	Top cable entry M32

#### Technical data

**IP degree of protection** IP65

#### Further technical details

<b>Weight</b>	170,00 g
<b>Operating temperature range (min, max)</b>	-40°C...+125°C

#### Material properties

<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747194327
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437


#### Packaging Information

<b>Sub-packaging weight</b>	0,85 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747194334

# Part number MHVN 24.32



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures** size "104.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD .....	64 poles + @ 51+53 *		
CT, CTS **)	64 poles + @ 57 *		
CDD .....	108 poles + @ 64+66 *		
CDE .....	46 poles + @ 83+85 *		
CSH .....	24 poles + @ 91+93 *		
CCE .....	24 poles + @ 100+104 *		
CNE, CSE, JCNE, JCSE	24 poles + @ 101 and 109 *		
CSS .....	24 poles + @ 122+123 *		
CTE, CTSE **)	24 poles + @ 129 *		
CMSE .....	10+2 (aux) poles + @ 139 *		
CMCE .....	10+2 (aux) poles + @ 138 *		
CX .....	4/8 poles + @ 155 *		
MIXO .....	6 modules 160+195 *		

insert centre distance: 104 x 27 mm  
\* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	<b>CHIN 24</b>	M		
surface mounting housing, high construction, with 2 levers	<b>MAPN 24.32</b>	32		
with pegs, side entry			<b>MHON 24.32</b>	32
with pegs, side entry, high construction			<b>MFON 24.32</b>	32
with pegs, side entry			<b>MHVN 24.32</b>	32
with pegs, side entry, high construction			<b>MFVN 24.32</b>	32

\*\*) only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

**CHIN 24**

**MAPN 24.32**

**MFON 24.32**

**MHON 24.32**

**MHVN 24.32**

## Notes