

Part number

MLFV 24 G25



Hood, IL-BRID series, with 2 levers, M25 top cable entry without adapter, size "104.27", high construction

Product description

| | |
|----------------------|------------------------|
| Product type | Hood |
| Series | IL-BRID |
| Closing type | With 2 levers |
| Size | Size 104.27 |
| Cable entry | Top cable entry M25 |
| Specification | High construction |

Technical data

| | |
|--------------------------------|--------------------|
| IP degree of protection | IP65 / IP66 / IP69 |
|--------------------------------|--------------------|

Further technical details

| | |
|---|----------------|
| Operating temperature range (min, max) | -40°C...+125°C |
|---|----------------|

Material properties

| | |
|------------------------------|--|
| Other materials | Lever: Polyamide (PA) and Stainless steel core Gasket: Rubber |
| Colour | RAL 7040 grey |
| RoHs conformity | Compliant |
| China RoHs - EFUP | E |
| REACH SVHC substances | No |

Approvals / Standards

| | |
|-----------------------|-----|
| Certifications | DNV |
|-----------------------|-----|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747288408 |
| eCl@ss 8.1 | 27440202 |
| ETIM 7.0 | EC000437 |

Packaging Information

| | |
|----------------------------------|-------------------|
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 5 Pcs |
| Sub-packaging EAN barcode | 8015747297189 |

Part number

MLFV 24 G25



Catalogue drawings

