


Part number

# PE 3255 PV



Mobile socket outlet, PLUSO series, 3 poles + N + PE, 5 h (black), 32 A, 347/600 ÷ 400/690 V

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Socket<br>Mobile  |
| <b>Series</b>         | PE...PV, PLUSO  |
| <b>N. of poles</b>    | 3 poles + N +  |
| <b>Clock position</b> | 5   |

#### Technical data

|                                |                     |
|--------------------------------|---------------------|
| <b>Current</b>                 | 32 A                |
| <b>Voltage</b>                 | 347/600 ÷ 400/690 V |
| <b>IP degree of protection</b> | IP44                |

#### Further technical details

|   |                 |
|---|-----------------|
| <b>Weight</b>                                 | 275,00 g        |
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C |

#### Material properties

|                              |  |
|------------------------------|--|
| <b>Colour</b>                | RAL 7035 grey, RAL 9005 black  |
| <b>RoHs conformity</b>       | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>China RoHs - EFUP</b>     | 50   |
| <b>REACH SVHC substances</b> | Yes<br>Lead  |
| <b>SCIP number</b>           | Ca7de37f-add8-4b77-9861-279c94903ade   |

#### Approvals / Standards

|                           |                   |
|---------------------------|-------------------|
| <b>Reference standard</b> | EN 60309-1 and -2 |
|---------------------------|-------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747067119 |
|-------------------|---------------|

#### Packaging Information

|                                  |                   |
|----------------------------------|-------------------|
| <b>Sub-packaging weight</b>      | 0,28 kg           |
| <b>Sub-packaging description</b> | Plastic packaging |
| <b>Sub-packaging quantity</b>    | 1 Pcs             |
| <b>Sub-packaging EAN barcode</b> | 8015747067126     |

Part number

# PE 3255 PV



Catalogue drawings

(16 / 32A) PE ... PV



| PE...PV         | A      | B     | Ø min | Ø max |    |
|-----------------|--------|-------|-------|-------|----|
| <b>16A</b> 2P+⊕ | 157,5  | 68    | 7     | 17    |    |
|                 | 3P+⊕   | 164,5 | 76    | 7     | 17 |
|                 | 3P+N+⊕ | 183,5 | 83    | 9     | 22 |
| <b>32A</b> 2P+⊕ | 200,5  | 87    | 9     | 22    |    |
|                 | 3P+⊕   | 200,5 | 87    | 9     | 22 |
|                 | 3P+N+⊕ | 200,5 | 91    | 9     | 22 |

Notes