


Part number

# PEW 1625 PV



Mobile socket outlet, PLUSO series, 3 poles + N + PE, 2 h (green), 16 A, > 50 V

Product description		Material properties	
<b>Product type</b>	Socket Mobile	<b>Colour</b>	RAL 7035 grey, RAL 6017 green
<b>Series</b>	PEW...PV, PLUSO	<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>Connection type</b>	Screw terminal connection	<b>China RoHs - EFUP</b>	50
<b>N. of poles</b>	3 poles + N + 	<b>REACH SVHC substances</b>	Yes Lead
<b>Clock position</b>	2	<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade
Technical data		Approvals / Standards	
<b>Current</b>	16 A	<b>Reference standard</b>	EN 60309-1 and -2
<b>Voltage</b>	> 50 V	General ordering information	
<b>IP degree of protection</b>	IP67	<b>EAN13 code</b>	8015747156813
Further technical details		Packaging Information	
<b>Weight</b>	260,00 g	<b>Packaging length</b>	255,00 mm
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging height</b>	195,00 mm
		<b>Packaging width</b>	245,00 mm
		<b>Packaging weight</b>	2,75 kg
		<b>Packaging volume</b>	12,18 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	10 Pcs
		<b>Packaging EAN code</b>	8015747083690

Part number

# PEW 1625 PV



Catalogue drawings

(16 / 32A) PEW ... PV



PEW...PV	A	B	ø min	ø max
<b>16A</b> 2P+⊖	145	77	7	16
3P+⊖	145	85	7	16
3P+N+⊖	145	93	8	24
<b>32A</b> 2P+⊖	162	97	8	24
3P+⊖	162	97	8	24
3P+N+⊖	162	105	8	24

Notes