


Part number

# PEW 3245 PI



Flush-mounting socket outlet, PLUSO series, 3 poles + N + PE, 4 h (yellow), 32 A, 57/100 ÷ 75/130 V, inclined

| Product description                           |   | Material properties                 |   |
|---|---|-------------------------------------|---|
| <b>Product type</b>                           | Socket<br>Flush-mounting  | <b>Colour</b>                       | RAL 7035 grey, RAL 1021 yellow  |
| <b>Series</b>                                 | PEW...PI, PLUSO   | <b>RoHs conformity</b>              | Compliant with exemption<br>6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                            | 3 poles + N +  | <b>China RoHs - EFUP</b>            | 50  |
| <b>Clock position</b>                         | 4   | <b>REACH SVHC substances</b>        | Yes<br>Lead   |
| <b>Size</b>                                   | Socket fixing centre distance 77 x 85 mm  | <b>SCIP number</b>                  | Ca7de37f-add8-4b77-9861-279c94903ade  |
| <b>Specification</b>                          | Inclined  | <b>Approvals / Standards</b>        |   |
| <b>Technical data</b>                         |   | <b>Reference standard</b>           | EN 60309-1 and -2   |
| <b>Current</b>                                | 32 A  | <b>General ordering information</b> |   |
| <b>Voltage</b>                                | 57/100 ÷ 75/130 V   | <b>EAN13 code</b>                   | 8015747074964   |
| <b>IP degree of protection</b>                | IP67  | <b>Packaging Information</b>        |   |
| <b>Further technical details</b>              |   | <b>Packaging length</b>             | 255,00 mm   |
| <b>Weight</b>                                 | 280,00 g  | <b>Packaging height</b>             | 195,00 mm   |
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C   | <b>Packaging width</b>              | 245,00 mm   |
|   |   | <b>Packaging weight</b>             | 3,14 kg   |
|   |   | <b>Packaging volume</b>             | 12,18 dm <sup>3</sup>   |
|   |   | <b>Packaging description</b>        | Carton box  |
|   |   | <b>Packaging quantity</b>           | 10 Pcs  |
|   |   | <b>Packaging EAN code</b>           | 8015747074971   |

Part number

# PEW 3245 PI



Catalogue drawings

(16 / 32A) PEW ... PI



| PEW ... PI | A      | B  | C   | D   | E  | F  | G   | H  | I    | X  | Y  |    |
|------------|--------|----|-----|-----|----|----|-----|----|------|----|----|----|
| <b>16A</b> | 2P+⊕   | 65 | 82  | 83  | 48 | 35 | 70  | 50 | 29   | 58 | 52 | 60 |
|            | 3P+⊕   | 65 | 82  | 87  | 48 | 37 | 78  | 58 | 30   | 65 | 52 | 60 |
|            | 3P+N+⊕ | 90 | 100 | 102 | 50 | 38 | 86  | 66 | 35   | 75 | 77 | 85 |
| <b>32A</b> | 2P+⊕   | 90 | 100 | 116 | 50 | 50 | 92  | 68 | 37   | 78 | 77 | 85 |
|            | 3P+⊕   | 90 | 100 | 116 | 50 | 50 | 92  | 68 | 37   | 78 | 77 | 85 |
|            | 3P+N+⊕ | 90 | 100 | 118 | 50 | 50 | 100 | 73 | 42.5 | 86 | 77 | 85 |

Notes