

Part number

# PK 32114 EB



Interlocked switched socket-outlet, PK series, 3 poles + PE, 11 h (red), 32 A, 440 ÷ 460 V, without fuse-carrier


Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7035 grey, RAL 3000 red
<b>Series</b>	PK..EB		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles +	<b>RoHs conformity</b>	50
<b>Clock position</b>	11	<b>China RoHs - EFUP</b>	50
<b>Specification</b>	Without fuse-carrier	<b>REACH SVHC substances</b>	Yes Lead
Technical data		<b>SCIP number</b>	F6799547-ab84-42f2-938f-233ba663766d
<b>Current</b>	32 A	Approvals / Standards	
<b>Voltage</b>	440 ÷ 460 V	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>IP degree of protection</b>	IP44	General ordering information	
Further technical details		<b>EAN13 code</b>	8015747080927
<b>Weight</b>	1.300,00 g	Packaging Information	
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Sub-packaging length</b>	290,00 mm
<b>IK rating (impact degree of protection)</b>	IK10	<b>Sub-packaging height</b>	125,00 mm
		<b>Sub-packaging width</b>	155,00 mm
		<b>Sub-packaging weight</b>	1,30 kg
		<b>Sub-packaging volume</b>	5,62 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Carton box
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747080934

Part number

# PK 32114 EB



Catalogue drawings



Notes