


Part number

PK 3265 PB5



Interlocked switched socket-outlet, PK series,
3 poles + N + PE, 6 h (red), 32 A, 200/346 ÷
240/415 V, E33 - DIII fuse carrier

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | PK..PB5 |
| N. of poles | 3 poles + N +  |
| Clock position | 6 |
| Specification | E33 - DIII fuse carrier |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 32 A |
| Voltage | 200/346 ÷ 240/415 V |
| IP degree of protection | IP55 |

Further technical details

| | |
|--|-----------------|
| Weight | 3.400,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | F6799547-ab84-42f2-938f-233ba663766d |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747081658 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|-----------------------|
| Packaging length | 400,00 mm |
| Packaging height | 310,00 mm |
| Packaging width | 670,00 mm |
| Packaging weight | 29,60 kg |
| Packaging volume | 83,08 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 8 Pcs |
| Packaging EAN code | 8015747081665 |
| Sub-packaging length | 150,00 mm |
| Sub-packaging height | 140,00 mm |
| Sub-packaging width | 380,00 mm |
| Sub-packaging weight | 3,70 kg |
| Sub-packaging volume | 7,98 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747081672 |

Part number

PK 3265 PB5



Catalogue drawings



| | A |
|---------------|------------|
| 2P+⊕ | 363 |
| 3P+⊕ | 370 |
| 3P+N+⊕ | 370 |

Notes