

Part number

RX 08 D5GM



Male modular insert, Mixo Megabit series, crimp connection, 8 poles, 1 module, 10 A 50 V 0,8 kV 3, shielded, with additional PE connection, HNM version, 1 cable entry

Product description	
Product type	Modular insert
Series	Mixo Megabit
Connection type	Crimp connection with shield
Gender	Male
N. of poles	8 poles
Size	1 module
Specification	1 cable entry Shielded, with additional PE connection, HNM version

Technical data	
Current	10 A
Voltage	50 V
Rated impulse withstand voltage	0,8 kV
Pollution degree	3
Rated voltage according to UL/CSA	50 V
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure

Further technical details	
Characteristics according to EN 61984	10 A 50 V 0,8 kV 3
Mating cycles	≥ 10000
Insulation resistance	≥ 10 GΩ
Contact resistance	≤ 3 mΩ
Weight	46,00 g
Operating temperature range (min, max)	-40 °C ... +85 °C
UL 94 flammability rating	V-0

Material properties	
Main material	Polycarbonate (PC)
Other materials	Shield: zinc alloy
Colour	RAL 7032 grey
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards	
Certifications	DNV
UL	ECBT2
cUL	ECBT8

General ordering information	
EAN13 code	8015747282888
eCl@ss 8.1	27440205
ETIM 7.0	EC000438



Packaging Information	
Packaging weight	0,56 kg
Packaging volume	1,24 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747282949
Sub-packaging length	116,00 mm
Sub-packaging height	113,00 mm
Sub-packaging width	142,00 mm
Sub-packaging weight	0,06 kg
Sub-packaging volume	1,86 dm ³
Sub-packaging description	Plastic bag
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747282956

Part number

RX 08 D5GM



Catalogue drawings



Notes