

Part number

# TM 16114 SIS



Interlocked switched socket-outlet, TM series, 3 poles + PE, 11 h (red), 16 A, 440 ÷ 460 V, sectionable fuse carrier 10 x 38 mm, without base box

#### Product description

|                |                                                                                               |
|----------------|-----------------------------------------------------------------------------------------------|
| Product type   | Interlocked switched socket-outlet                                                            |
| Series         | TM.. SIS/KSIS                                                                                 |
| N. of poles    | 3 poles +  |
| Clock position | 11                                                                                            |
| Specification  | Sectionable fuse carrier 10 x 38 mm<br>Without base box                                       |

#### Technical data

|                         |             |
|-------------------------|-------------|
| Current                 | 16 A        |
| Voltage                 | 440 ÷ 460 V |
| IP degree of protection | IP66 / IP67 |

#### Further technical details

|                                         |                 |
|-----------------------------------------|-----------------|
| Operating temperature range (min, max)  | -25°C ... +40°C |
| UL 94 flammability rating               | V-2             |
| IK rating (impact degree of protection) | IK10            |

#### Material properties

|        |                             |
|--------|-----------------------------|
| Colour | RAL 7012 grey, RAL 3000 red |
|--------|-----------------------------|

#### Approvals / Standards

|                    |                     |
|--------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|--------------------|---------------------|

#### General ordering information


|            |               |
|------------|---------------|
| EAN13 code | 8015747160643 |
|------------|---------------|

Part number

# TM 16114 SIS



Catalogue drawings



|               | <b>A</b> | <b>B</b> |
|---------------|----------|----------|
| <b>2P+⊕</b>   | 83       | 276      |
| <b>3P+⊕</b>   | 85       | 276      |
| <b>3P+N+⊕</b> | 90       | 277      |

Notes