


Part number

# TM 1664 SPX



Interlocked switched socket-outlet, TM ATEX series, 3 poles + PE, 6 h (red), 16 A, 380 ÷ 415 V, sectionable fuse carrier 10 x 38 mm, with base box

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7012 grey, RAL 3000 red
<b>Series</b>	TM ATEX		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles + 	<b>RoHs conformity</b>	6(c): copper alloy containing up to 4% lead by weight
<b>Clock position</b>	6	<b>China RoHs - EFUP</b>	50
<b>Size</b>	114 x 255 mm fixing distance, for assembly in plates TM xx45 TB	<b>REACH SVHC substances</b>	Yes Lead
<b>Specification</b>	Sectionable fuse carrier 10 x 38 mm With base box	<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
Technical data		Approvals / Standards	
<b>Current</b>	16 A	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>Voltage</b>	380 ÷ 415 V	General ordering information	
<b>IP degree of protection</b>	IP66 / IP67	<b>EAN13 code</b>	8015747199018
Further technical details		Packaging Information	
<b>Weight</b>	1,11 g	<b>Packaging volume</b>	52,36 dm <sup>3</sup>
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging description</b>	Carton box
<b>IK rating (impact degree of protection)</b>	IK10	<b>Packaging quantity</b>	9 Pcs
		<b>Packaging EAN code</b>	8015747199025
		<b>Sub-packaging description</b>	Plastic packaging
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747199032

Part number

**TM 1664 SPX**



---

Notes