

Part number

TM 1665 ISX



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 6 h (red), 16 A, 200/346 ÷ 240/415 V, sectionable fuse carrier 10 x 38 mm, with base box

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 3000 red
Series	TM ATEX	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + N + 	China RoHs - EFUP	50
Clock position	6	REACH SVHC substances	Yes Lead
Size	114 x 255 mm fixing distance, for assembly in plates TM xx45 TB	SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Specification	Sectionable fuse carrier 10 x 38 mm With base box	Approvals / Standards	
Technical data		Reference standard	EN 60309-1, -2 e -4
Current	16 A	General ordering information	
Voltage	200/346 ÷ 240/415 V	EAN13 code	8015747103251
IP degree of protection	IP66 / IP67	Packaging Information	
Further technical details		Packaging weight	14,58 kg
Weight	1.620,00 g	Packaging volume	55,44 dm ³
Operating temperature range (min, max)	-25°C ... +40°C	Packaging description	Carton box
UL 94 flammability rating	V-2	Packaging quantity	9 Pcs
IK rating (impact degree of protection)	IK10	Packaging EAN code	8015747103268
		Sub-packaging weight	1,62 kg
		Sub-packaging description	Plastic packaging
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747103275

Part number

TM 1665 ISX



Notes