


Part number

TM 1675 SIT



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 7 h (black), 16 A, 277/480 ÷ 288/500 V, E16 fuse carrier, without base box

| Product description | |
|--|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM.. SIT |
| N. of poles | 3 poles + N +  |
| Clock position | 7 |
| Specification | E16 fuse carrier Without base box |
| Technical data | |
| Current | 16 A |
| Voltage | 277/480 ÷ 288/500 V |
| IP degree of protection | IP66 / IP67 |
| Further technical details | |
| Weight | 1.300,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|----------------------------------|-------------------------------|
| Colour | RAL 7012 grey, RAL 9005 black |
| Approvals / Standards | |
| Reference standard | EN 60309-1, -2 e -4 |
| General ordering information | |
| EAN13 code | 8015747090407 |
| Packaging Information | |
| Sub-packaging weight | 1,30 kg |
| Sub-packaging description | Carton tray |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747108508 |

Part number

TM 1675 SIT



Catalogue drawings



| | A | B |
|---------------|----------|----------|
| 2P+⊕ | 83 | 276 |
| 3P+⊕ | 85 | 276 |
| 3P+N+⊕ | 90 | 277 |

Notes