


Part number

# TM 3273KIR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 7 h (black), 32 A, 480 ÷ 500 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

Product description	
<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	TM..IR/KIR
<b>N. of poles</b>	2 poles + 
<b>Clock position</b>	7
<b>Specification</b>	With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box
Technical data	
<b>Current</b>	32 A
<b>Voltage</b>	480 ÷ 500 V
<b>IP degree of protection</b>	IP66 / IP67
Further technical details	
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>UL 94 flammability rating</b>	V-2
<b>IK rating (impact degree of protection)</b>	IK10

Material properties	
<b>Colour</b>	RAL 7012 grey, RAL 9005 black
Approvals / Standards	
<b>Reference standard</b>	EN 60309-1, -2 e -4
General ordering information	
<b>EAN13 code</b>	8015747163224

Part number

# TM 3273KIR



Catalogue drawings



	A	B
<b>2P+⊕</b>	133	276
<b>3P+⊕</b>	135	276
<b>3P+N+⊕</b>	140	277

Notes