


Part number

# TM 63115 IR



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 11 h (red), 63 A, 250/440 ÷ 265/460 V, with compartment for modular units, 6 DIN-rail modules EN 60715, with base box

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | TM..IR/KIR  |
| <b>N. of poles</b>    | 3 poles + N +  |
| <b>Clock position</b> | 11  |
| <b>Specification</b>  | With compartment for modular units, 6 DIN-rail modules EN 60715<br>With base box                |

#### Technical data

|                                |                     |
|--------------------------------|---------------------|
| <b>Current</b>                 | 63 A                |
| <b>Voltage</b>                 | 250/440V ÷ 265/460V |
| <b>IP degree of protection</b> | IP66 / IP67         |

#### Further technical details

|  |                               |
|--|-------------------------------|
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C               |
| <b>UL 94 flammability rating</b>               | V-0 (insert), V-2 (enclosure) |
| <b>IK rating (impact degree of protection)</b> | IK10                          |

#### Material properties

|               |                             |
|---------------|-----------------------------|
| <b>Colour</b> | RAL 7012 grey, RAL 3000 red |
|---------------|-----------------------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747163460 |
|-------------------|---------------|

Part number

# TM 63115 IR



Catalogue drawings



Notes