

Codice articolo

MAPN 24.32



Custodia da parete, serie LS-TYPE, con 2 leve, ingresso cavo M32, grandezza "104.27", alta

Descrizione prodotto

Tipo prodotto	Custodia da parete
Serie	LS-TYPE
Tipo chiusura	Con 2 leve
Grandezza	Grandezza 104.27
Ingresso cavo	Con ingresso cavo M32
Specifica	Alta

Dati tecnici

Grado di protezione IP	IP65
-------------------------------	------

Ulteriori dettagli tecnici

Peso	444,00 g
Temperature di esercizio (min, max)	-40°C...+125°C

Proprietà dei materiali

Altri materiali	Leva: Poliammide (PA) Guarnizione: NBR
Colore	Nero RAL 9005
Conformità RoHs	Conforme
China RoHs - EFUP	E
Sostanze REACH SVHC	No

Approvazioni / Normative

Certificazioni	DNV, BV
UL	ECBT2
cUL	ECBT8

Informazioni commerciali

Codice EAN13	8015747163149
Classificazione ecl@ss	27440202
Classificazione ETIM	EC000437

Caratteristiche imballaggio

Lunghezza imballo	305,00 mm
Altezza imballo	180,00 mm
Profondità imballo	275,00 mm
Peso imballo	4,96 kg
Volume imballo	15,10 dm ³
Descrizione imballo	Scatola cartone
Quantità imballo	10 pz
Codice EAN13 imballo	8015747250207
Peso sottoimballo	2,48 kg
Descrizione sottoimballo	Termoretraibile
Quantità sottoimballo	5 pz
Codice EAN13 sottoimballo	8015747187671

Codice articolo MAPN 24.32



Disegni da catalogo



Disegni da catalogo

CH..N - MA, MF..N enclosures size "104.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD	64 poles + @ 51+53 *		
CT, CTS **)	64 poles + @ 57 *		
CDD	108 poles + @ 64+66 *		
CDE	46 poles + @ 83+85 *		
CSH	24 poles + @ 91+93 *		
CCE	24 poles + @ 100+104 *		
CNE, CSE, JCNE, JCSE	24 poles + @ 101 and 109 *		
CSS	24 poles + @ 122+123 *		
CTE, CTSE **)	24 poles + @ 129 *		
CMSE	10+2 (aux) poles + @ 139 *		
CMCE	10+2 (aux) poles + @ 138 *		
CX	4/8 poles + @ 155 *		
MIXO	6 modules 160+195 *		

insert centre distance: 104 x 27 mm
* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	CHIN 24	M		
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32		
with pegs, side entry			MHON 24.32	32
with pegs, side entry, high construction			MFON 24.32	32
with pegs, side entry			MHVN 24.32	32
with pegs, side entry, high construction			MFVN 24.32	32

**) only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 24

MAPN 24.32

dimensions in mm

MFON 24.32

MFVN 24.32

MHON 24.32

MHVN 24.32

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.